



Article MADRAS

- thickness 0,9 - 1,1 mm
- print Madras
- cow or buffalo leather

TECHNICAL PARAMETERS

No	Test	Method	Unit	Requirement
1	Thickness of finish	ČSN EN ISO 2589	mm	-
2	Density	DIN 53327	g/cm ³	-
3	Water vapour permeability	IUP 15	mg/cm ² h	-
4	Tear strenght	ČSN EN ISO 3377-2	N	min 40
5	Cold crack resistance of finish	IUP 29	Verbal description	No cracking at -10°C
6	Finish adhesion	ISO 11644	N/10 mm	min 2
7	Colour fastness to rubbing 500 cycles Dry	ČSN EN ISO 11640, ISO 11641	Grey scale	min 4
	Colour fastness to rubbing 250 cycles Wet		Grey scale	min 3
	Colour fastness to rubbing 80 cycles Perspiration		Grey scale	min 3
8	Colour fastness to light	Internal Norm FZ-U-793856	Blue scale	min 5
9	Formaldehyde	ČSN EN ISO 14184-1	mg/kg	max 30
10	Chromium	ČSN 793873	mg/kg	max 50
11	Chromium VI	ČSN EN 420 čl.6.1.	mg/kg	max 0,5
12	pH	ČSN ISO 4045	-	3,5 - 8,5